



## AXT910, AXT920, and AXT920SL Batteries



AXT910 Bodypack Battery



AXT920, AXT920SL Handheld Battery



### WARNING

- Battery packs may explode or release toxic materials. Risk of fire or burns. Do not open, crush, modify, disassemble, heat above 140°F (60°C), or incinerate
- Follow instructions from manufacturer
- Never put batteries in mouth. If swallowed, contact your physician or local poison control center
- Do not short circuit; may cause burns or catch fire
- Do not charge or use battery packs with other than specified Shure products
- Dispose of battery packs properly. Check with local vendor for proper disposal of used battery packs

## Shure Rechargeable Batteries

The AXT910, AXT920, and AXT920SL are rechargeable lithium-ion transmitter batteries.

## Storing Batteries

Store batteries in the charger when not in use. If batteries are to be stored for more than eight days, they should be removed from the charger and placed into a temperature controlled storage area. Recommended battery storage temperature is 10°C (50°F) to 25°C (77°F).

## Certifications

Meets essential requirements of the following European Directives:

- EMC Directive 2004/108/EC
- Battery Directive 2006/66/EC

Please follow your regional recycling scheme for battery disposal.

## Specifications

Battery Type	Rechargeable Li-Ion	
Nominal Capacity	AXT910:	1900 mAh (7.03 Wh)
	AXT920/920SL:	2450 mAh (8.82 Wh)
Nominal Voltage	AXT910:	3.7 V
	AXT920/920SL:	3.6 V
Dimensions	AXT910:	17 mm x 69 mm x 43 mm, H x W x D
	AXT920/920SL:	21 mm x 76 mm x 26 mm, H x W x D
Weight	AXT910:	74 g (2.6 oz.)
	AXT920/920SL:	63 g (2.2 oz.)
Housing	AXT910:	Molded ABS, Cast Aluminum
	AXT920/920SL:	Molded ABS
Charging Temperature Range	0°C (32°F) to 60°C (140°F)	
Discharging Temperature Range	-18°C (0°F) to 60°C (140°F)	
Recommended Storage Temperature Range	10°C (50°F) to 25°C (77°F)	



### United States, Canada, Latin America, Caribbean:

Shure Incorporated  
5800 West Touhy Avenue  
Niles, IL 60714-4608 USA

Phone: 847-600-2000  
Fax: 847-600-1212 (USA)  
Fax: 847-600-6446  
Email: info@shure.com

### Europe, Middle East, Africa:

Shure Europe GmbH  
Jakob-Dieffenbacher-Str. 12,  
75031 Eppingen, Germany

Phone: 49-7262-92490  
Fax: 49-7262-9249114  
Email: info@shure.de

### Asia, Pacific:

Shure Asia Limited  
22/F, 625 King's Road  
North Point, Island East  
Hong Kong

Phone: 852-2893-4290  
Fax: 852-2893-4055  
Email: info@shure.com.hk